

AMBASSADEURS ROSSIGNOL BIKES



SPECS E-BIKES

Nom	E-Track 24	E-Track Fat	E-Track 27+	E-Track Trail
Code Produit	RMH0016	RMH5012	RMH5003	RMH5001
Couleur	Orange (Cyan,Grey,White)	Black(Yellow)	Red & Black	Black & Red
Taille	1 Size	1 size	SM, MD, LA, XL	SM, MD, LA, XL
Cadre	24" wheel kids E-Bike design for Shimano drive unit, 6061 hydroform Aluminum, tapered head tube, IS disc brake mounts, Dropouts w/double eyelets, euro 68mm BB, 135mm OLD, 27.2 seat post, 31.8mm FD clamp	EVO Fat Bike Alloy 26" internal cable routing	Felt 27.5+ Surplus-e Shimano Specific E-Bike frame, Fully integrated down tube, Boost 148x12mm rear OLD and slacker head angle, post mount disc, Ø31.6mm seatpost size	Felt 27.5+ Redemption, Shimano double-butted 6061 aluminum, Hydroform, 140mm travel, Fully integrated battery, ControlTaper head tube, disc brake specific, replaceable derailleur hanger, Boost 12 / 148mm, full internal cable routing, Ø31.6mm seatpost size
Moteur	Shimano E-6000 Drive unit 25KPH	New Brose 250W limited at 27km/h	Shimano e8000 MTB drive, 250 W output, 25 Km/h (eu-rope), 20m/h (Noram)	Shimano e8000 MTB drive, 250 W output, 25 Km/h (eu-rope), 20m/h (Noram)
Suspension arrière	N/A	N/A	N/A	Rock Shox Deluxe R, DEBONAIR, 185X52.5 Trunion mount
Fourche	SR Suntour XCT-JR 80mm travel	"RockShox Bluto RL, 15x150 100mm"	Rock Shox Recon RL. Solo Air, 130mm, Boost 15 / 110mm thru axle	SR Suntour Aion, Air, Boost 110mm thru axle
JDD	FSA Orbit 1.5 zerostack 1.5-1 1/8 reducer NO.57-1	Integrated Headset	Integrated Headset	Integrated Headset
Potence	MTB 3D-forged threadless 1-1/8" +/- 10° rise w/ black Cr-Mo bolts,	Alloy 31,8mm, Angle 6°. Size M/L: 60mm,	Alloy 31,8mm, Angle 6°. Size M/L: 60mm,	Alloy 31,8mm, Angle 6°. Size M/L: 60mm
Guidon	MTB 6061 Flat bar, Ø31.8mm, 10mm rise x 5° sweep 600mm	Alloy Bar Bore:31,8mm Width:740mm	Alloy Bar Bore:31,8mm Width:780mm	Alloy Bar Bore:31,8mm Width:780mm
Grip	MTB design single density rubber	MTB design single density rubber	MTB design single density rubber	MTB design single density rubber
Mannette	SRAM X5 9-speed	New Shimano Deore 1X10	New Shimano Deore 1X10	New Shimano Deore 1X10
Dérailleur avant	N/A	N/A	N/A	N/A
Dérailleur arrière	SRAM X5 mid cage	shimano Deore 1X10	Shimano Deore M6000	Shimano Deore M6000
Pédalier	Forged Alloy, Square Tapered 152mm	"FSA Plateau 36 D"	Shimano Forged alloy	Shimano Forged alloy
Couronne	38T		34T	34T
Guide chaîne	N/A	BH Chain guide	N/A	N/A
Boîtier de pédalier	N/A	N/A	N/A	N/A
Pédales	Kids design	MTB Design	MTB Design	MTB Design
Batterie	Shimano e8010 500wh	500wh	Shimano E8020 500wh	Shimano E8020 500wh
Chaîne	SRAM PC-951	Shimano CN-E6090	Shimano	Shimano
Cassette	SRAM PG-950, 11-34, cassette	Shimano CS-HG500 11/42	Shimano 11/42	Shimano 11/42
Levier de frein	Shimano 315	Shimano	Shimano Deore	Shimano Deore
Frein (avant)	Shimano M315 hydraulic w/160mm rotor	Shimano M396 200mm	Shimano M6000 200mm	Shimano M6000 200mm
Frein (arrière)	Shimano M315 hydraulic w/160mm rotor	Shimano M396 180mm	Shimano M6000 180mm	Shimano M6000 180mm
Cables	Sealed slick cables	Slick internal cable	Slick internal cable	Slick internal cable
Selle	MTB kids design	Rossignol Design	Rossignol Design	Rossignol Design
Tige de selle	Butted 6061, dual-bolt micro-adjust 15mm offset, Ø30.9; 250mm	N/A	Aluminum micro adjust, 31,6mm; 350mm (SM) & 400mm (MD, LG, XL)	KS E-TEN
Collier de selle	Alloy Cold forged 31.8 w/ QR lever	Alloy Cold forged QR lever	Alloy Cold forged QR lever	Alloy Cold forged QR lever
Jante / roue	Aluminum double-wall, 24mm inner	Alloy Double Wall Fat Light	WTB Scaper i35 rims tubeless	WTB Scaper i35 rims tubeless
Moyeu avant	Forged Aluminum, 6-bolt, QRx100	Forged Aluminum	Shimano Deore, Centerlock, 15x110	Shimano Deore, Centerlock, 15x110
Moyeu arrière	Forged Aluminum, 6-bolt, QRx135	Forged Aluminum	Shimano Deore, Centerlock, 12x148	Shimano Deore, Centerlock, 12x148
Rayons	2.0 stainless steel	front 14G regular spoke+ rear with nylock. Front without nylock	Stainless steel	Stainless steel
Pneux	Kenda K-Rad 24x2.35	Kenda 26"x4.0	Maxxis Rekon +, exo, Dual, 27,5x2.8	Maxxis Minion DHF 27,5x2.8 EXO ,High Roller 2 exo rear